






- NOTES:
1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL CODES.
 2. PLEASE REFER TO PRODUCT DOCUMENTATION FOR FURTHER INFORMATION.
 3. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS (INCHES).
 4. MOUNTING BUTTON IS AN ALTERNATIVE MOUNTING METHOD TO THE TOOLLESS MOUNT FOR 3RD PARTY ENCLOSURE. BUTTON IS PROVIDED WITH THE UNIT. DETAILED INSTALLATION INSTRUCTIONS CAN BE FOUND IN THE PROVIDED MANUAL.
 5. BRACKET KITS TO MOUNT TO SPECIFIC 3RD PARTY ENCLOSURES ARE AVAILABLE AS OPTIONS.
 6. RARITAN STANDARD LENGTH OF THE CORD IS 3000MM +/- 70MM
 7. DIMENSION TOLERANCE: LENGTH +/- 3MM, WIDTH +/- 1MM, DEPTH +/- 0.5MM

Raritan A brand of legrand		PROJECTION THIRD ANGLE	DO NOT SCALE DRAWING SHEET 1 OF 1	SPECIFICATION iPDU Zero U 380-415V 3Φ-Y, 16A Plug Type: IEC60309 16A 3PY Outlet Type: Locking C13 (12), Locking CX (12)	
Drawing Maker: Eva Lin	Sep. 19, 2023	THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF RARITAN, Inc. AND SHALL NOT BE COPIED, REPRODUCED OR USED, IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM RARITAN, Inc. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.		DWG NO. MPX4-5538-E7 & MPX4-5538-E7M18 & MPX4-5538-E7M28	REV. 0B
Design Engineer: Sam Liu	Sep. 19, 2023			MODEL NO. PX4-5538-E7 & PX4-4538-E7 PX4-5538-E7M18 & PX4-5538-E7M18 PX4-5538-E7M28 & PX4-4538-E7M28	
Approver: Tom Hsueh	Sep. 19, 2023				