







- NOTES:
1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL CODES.
 2. PLEASE REFER TO PRODUCT DOCUMENTATION FOR FURTHER INFORMATION.
 3. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS (INCHES).
 4. MOUNTING BUTTON IS AN ALTERNATIVE MOUNTING METHOD TO THE TOOLLESS MOUNT FOR 3RD PARTY ENCLOSURE. BUTTON IS PROVIDED WITH THE UNIT. DETAILED INSTALLATION INSTRUCTIONS CAN BE FOUND IN THE PROVIDED MANUAL.
 5. BRACKET KITS TO MOUNT TO SPECIFIC 3RD PARTY ENCLOSURES ARE AVAILABLE AS OPTIONS.
 6. RARITAN STANDARD LENGTH OF THE CORD IS 3000MM +/- 70MM
 7. DIMENSION TOLERANCE: LENGTH +/- 3MM, WIDTH +/- 1MM, DEPTH +/- 0.5MM

Raritan® A brand of 		 PROJECTION THIRD ANGLE	DO NOT SCALE DRAWING SHEET 1 OF 1		SPECIFICATION		
					iPDU Zero U 380-415V 3Φ-Y, 32A Plug Type: IEC60309 32A 3PY Outlet Type: Locking HDOT C13 (18), Locking CX (18)		
Drawing Maker: Eva Lin	Oct. 11, 2024		THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF RARITAN, Inc. AND SHALL NOT BE COPIED, REPRODUCED OR USED, IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM RARITAN, Inc. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.		DWG NO.	MPX4-5699-E7M18V2 & MPX4-5699-E7M27V2 & MPX4-5699-E7M28V2	
Design Engineer: Eva Lin	Oct. 11, 2024				MODEL NO.	PX4-5699-E7M18V2 & PX4-4699-E7M18V2 PX4-5699-E7M27V2 & PX4-4699-E7M27V2 PX4-5699-E7M28V2 & PX4-4699-E7M28V2	REV. 0C
Approver: Tom Hsueh	Oct. 11, 2024						